

# THE ESSENCE OF SMART, SIMPLE AND SECURE.

Our new flagship roll-up garage door opener, the EasyRoller® Gen2 expands on the international standard set by its predecessor. Retaining the proven slimness, technological performance and reliability, this new opener introduces key technologies including Wireless Safety Beam compatibility and LED lighting.

The EasyRoller® Gen2 takes forward the impressive reputation earned by this series of openers over the past decade. This new version incorporates bright LED courtesy lighting and compatibility with Wireless Safety Beams. Also, the Service Indicator lets you know when it is time to service your door. This is in addition to TrioCode™128 transmitters for security, Soft Start/Soft Stop for quietness, advanced door profiling and obstruction sensing for safe, reliable operation.

# WHAT'S IN THE BOX:



Opener with LED Courtesy Lights



Easy Access Transmitter to open and close the door from within the garage



Two TrioCode<sup>™</sup>128 transmitters

# **AT A GLANCE:**



# SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 transmitter system ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes\*) for the ultimate in security.

\*340,282,366,920,938,463,463,374,607,431,768,211,456 code:

### **POWERFUL MOTOR**

A powerful DC 600N motor means this opener is both consistent and reliable, and we back this up with a five year warranty.

### **LED COURTESY LIGHT**

A Courtesy Light means your immediate surrounds can be lit to provide security and convenience, and being an LED light source you know it's going to last.

# **5-YEAR WARRANTY**

The EasyRoller® Gen2 is backed by a 5-year/10,000 cycle warranty, giving peace-of-mind that you are choosing the most reliable automation solution.

SMART SIMPLE SECURE

# TECHNICAL SPECIFICATIONS

Power	Input Voltage	230-240V a.c. 1-phase
	Transformer Rating	100VA
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Peak Driving Force	600N
Door Sizes	Rated Door Area	16.5m²
	Typical Travel Speed	130mm/sec
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 <sup>38</sup> code combinations (340,282,366,920,938,463,463,374,607,431,768,211,456 codes)
	Transmitter Type	TrioCode <sup>™</sup> 128
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	2 x LED
	Safety Beam Compatibility	2 x Wireless/2-wire Safety Beams
Warranty		5 year/10,000 cycles

# **SAFETY & SECURITY FEATURES**



Soft Start/Soft Stop



**Intelligent Safety System** 



**Door Profiling** 



TrioCode™128



## **POWER & MOUNTING SYSTEMS**



DC Motor - 600N



Slim Fit

## **OPERATING MODES & FEATURES**



Wireless Safety Beam Ready



**LED Courtesy Lights** 



Auto Close (with Safety Beams)



Service Indicator



Ventilation Mode



Vacation Mode



**Auxiliary Output** 

See our website for our icon glossary explanations.

### **Proudly Distributed by:**

# ENHANCE YOUR OPENER TO MATCH YOUR LIFESTYLE



Battery Back Up In the event of power failure your door will still work



SmartSolar™ Ready Using only one solar panel the sun does all the work for you



Wireless Safety Beams Extra peace of mind that protects children and pets, plus enables Auto-Close



www.facebook.com/ATA.Openers