

automatic
TECHNOLOGY

GDO-11 ErO
automatic
TECHNOLOGY
smart | simple | secure



ERO[®] GDO-11

TECHNOLOGY ON A BUDGET

THE STANDARD IN QUIET, QUICK AND VALUE FOR MONEY

The Ero[®] offers a leading edge garage door opener at a value for money price. With all the important features included, and a 650N DC motor that will drive most standard residential sectional doors, this is the entry level opener to make your automation desires a reality.

It's the choice for new homebuyers and for all the right reasons. It comes standard with the really important features of TrioCode™128, Intelligent Safety System, Door Profiling and Soft Start/Soft Stop. It also includes a Standard Courtesy Light, and importantly a service indicator to remind you when your door needs servicing.

WHAT'S IN THE BOX:



Opener with Courtesy Light




Two TrioCode™128 transmitters

AT A GLANCE:



SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 transmitter system ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes*) for the ultimate in security.



*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

POWERFUL MOTOR

A reliable 650N DC motor means this door is both consistent and reliable, and we back this up with a two year guarantee.

COURTESY LIGHT

A built in Courtesy Light means your immediate surrounds can be lit to provide security and convenience.

INTELLIGENCE

This opener has built-in intelligent features such as Intelligent Safety System, Door Profiling and Soft Start/Soft Stop – meaning the door adjusts itself when opening and closing or if blocked.

SMART
SIMPLE
SECURE

ERO[®] GDO-11

TECHNICAL SPECIFICATIONS



Power	Input Voltage	230-240V a.c. 1-phase
	Transformer Rating	72VA
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Peak Driving Force	650N
Door Sizes	Rated Door Area	13.5m ²
	Typical Travel Speed (door dependent)	140mm/sec
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 ³⁸ code combinations <small>(340,282,366,920,938,463,463,374,607,431,768,211,456 codes)</small>
	Transmitter Type	TrioCode™128
	Transmitter Capacity (x4-button registers)	8
Additional Features	Courtesy Light	1 x Festoon Globe
	Safety Beam Compatibility	1 x 3-wire PE Beam
Warranty		2 year/5,000 cycles

SAFETY & SECURITY FEATURES



Soft Start/Soft Stop



Intelligent Safety System



Door Profiling



128
TrioCode™128



POWER & MOUNTING SYSTEMS



DC Motor - 650N



Low Headroom

OPERATING MODES & FEATURES



Standard Courtesy Light



Service Indicator



AUX Auxiliary Output

See our website for our icon glossary explanations.

ENHANCE YOUR OPENER TO MATCH YOUR LIFESTYLE



Wireless Keypad Weatherproof, secure access without a transmitter or keys is great for school kids and active families.



Wired Safety Beams (3-wire) Using legacy 3-wire technology, these safety beams help protect your family and possessions.

Proudly Distributed by:

www.automatictechnology.com.au



www.facebook.com/ATA.Openers

SMART
SIMPLE
SECURE

©2013 Automatic Technology (Australia) Pty Ltd. All rights reserved. The Automatic Technology logos, "smart simple secure" wordage, feature icons, Ero™ & TrioCode™ are trademarks and registered trademarks of Automatic Technology (Australia) Pty Ltd. No part of this brochure may be reproduced without prior permission. In an ongoing commitment to product quality we reserve the right to change specification without notice. E&OE. 6-8 Fiveways Boulevard, Keysborough, Victoria, 3173. Ph: +61 (0) 3 9791 0200. Fx: +61 (0) 3 9791 0250. Printed Oct 2013. 204603 ATA Ero™GDO-11.

For more information on this door opener and other Automatic Technology products please visit us online.

automatic
TECHNOLOGY